

## FLUXO S190 - CLEANER

Piece degreasing & cleaning of penetrant excess.

### Direction for use:


Spray FLUXO S190 - CLEANER until disappearance of red or purple PENETRANT traces.

### Safety precautions:

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Irritating to skin. Extremely flammable. Vapours may cause drowsiness and dizziness. Keep away from sources of ignition - no smoking. Do not breathe the steams. Avoid release to the environment. Refer to special instructions/Safety data sheets. Pressurised container: protect from sunlight and do not expose to temperatures

exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. If swallowed, seek medical advice immediately and show this container or label.

- Propellant: Butane / Propane.
- Volume : 500 ml (net) - 650 ml (nominal).




Cat N°: P00026667

## FLUXO P125 - PENETRANT

Non destructive testing.

### Direction for use:

Be sure the area is clean. Spray at 20 cm FLUXO P125 - PENETRANT for a complete recover of the area. Let penetrate at least 10 minutes. Rinse with FLUXO S190 - CLEANER. Control with FLUXO R175 - DEVELOPER.



### Safety precautions:

Suitable for temperatures: 0 °C to 50 °C. Extremely flammable. Keep away from sources of ignition - no smoking. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or

burn, even after use. Do not spray on a naked flame or any incandescent material. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas. Do not breathe vapors.

- Propellant: Butane / Propane.
- Volume : 500 ml (net) - 650 ml (nominal).



Cat N°: P00026665

## FLUXO R175 - DEVELOPER

Detection of cracks and surface faults.

### Direction for use:


Be sure that the area is clean and without penetrant last trace. Shake the can until hearing clearly the ball bearing. Spray at 20 cm for an uniform layer without super thickness. Wait a few minutes until obtaining a dry powdery film before examining the surface.

### Safety precautions:

Irritating to eyes. Extremely flammable. Vapours may cause drowsiness and dizziness. Keep away from sources of ignition - no smoking. Do not breathe the steams. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame

or any incandescent material. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas.

- Propellant: Butane / Propane.
- Volume : 500 ml (net) - 650 ml (nominal).



Cat N°: P00026772

### Also available: ARDROX

- |                         |                   |
|-------------------------|-------------------|
| • ARDROX 9PR5 CLEANER   | Cat N°: P00026631 |
| • ARDROX 9VF2 PENETRANT | Cat N°: P00026664 |
| • ARDROX NQ1 DEVELOPER  | Cat N°: P00026632 |